



Localization of NetarchiveSuite

How to translate the NetarchiveSuite interface into your own language



Outline

- Java and i18n localization
- NetarchiveSuite use of localization
- Files containing translations
- Settings used for localization



Java and i18n localization

- Java supports localization of number formats, date formats, and currencies, as well as translations of strings
- Translation of strings are stored in Java properties files
- Translated strings may contain parameters



Java and i18n localization - example

Translations_en.properties:

```
bytes.on.date=On {0, date} you  
have harvested {1} bytes
```

Translations_de.properties:

```
bytes.on.date=Sie haben {1} Bytes  
an {0, date} geerntet
```



Java and i18n localization

- English:

On Sep 4, 2007 1:10:45 PM you
have harvested 2,324,210 bytes

- German

Sie haben 2.324.210 Bytes an
04.09.2007 13:10:45 geerntet



NetarchiveSuite use of localization

- The user interface is fully localized
- Currently supports Danish and English translations
- Exceptions and log messages are **not** localized, English only
- Unexpected exception scenarios may reach the user interface



Files containing translations

- For each module, there are three files:
 - Translations.properties :
default translations, English
 - Translations_da.properties
Danish translations
 - Translations_en.properties
English translations, to force fall back to
default translations



Files containing translations

```
./dk/netarkivet/viewerproxy/Translations_da.properties  
./dk/netarkivet/viewerproxy/Translations.properties  
./dk/netarkivet/viewerproxy/Translations_en.properties  
./dk/netarkivet/common/Translations_da.properties  
./dk/netarkivet/common/Translations.properties  
./dk/netarkivet/common/Translations_en.properties  
./dk/netarkivet/archive/Translations_da.properties  
./dk/netarkivet/archive/Translations.properties  
./dk/netarkivet/archive/Translations_en.properties  
./dk/netarkivet/monitor/Translations_da.properties  
./dk/netarkivet/monitor/Translations.properties  
./dk/netarkivet/monitor/Translations_en.properties  
./dk/netarkivet/harvester/Translations_da.properties  
./dk/netarkivet/harvester/Translations.properties  
./dk/netarkivet/harvester/Translations_en.properties
```



Settings used by localization

- The user interface needs to know
 - which translations are present
 - the name of the language

```
<settings><common><web interface>

  <language>
    <!-- A locale the GUI is available as -->
    <locale>da</locale>
    <!-- Native name of the language for this locale -->
    <name>Dansk</name>
  </language>
  ...
</webinterface></common></settings>
```



Adding your language

- Unpack translations from the jar-file you wish to localize:

```
jar xf lib/dk.netarkivet.harvester.jar  
dk/netarkivet/harvester/Translations.properties
```

- Rename to translations to your locale:

```
mv dk/netarkivet/harvester/Translations.properties  
dk/netarkivet/harvester/Translations_de.properties
```

- Open the file in a text editor and change the strings to your language

- Add the new file to the jar-file:

```
jar uf lib/dk.netarkivet.harvester.jar  
dk/netarkivet/harvester/Translations_de.properties
```



Adding your language

- Open settings.xml
- Find the <language> section
- Add your language:

```
<language>
  <locale>de</locale>
  <name>Deutsch</name>
</language>
```



Adding your language

- You are done!
- Please send us your translations